

# ZXT-310

## Z-Wave to AV IR Extender

Control your traditional AV devices through Z-Wave



### Benefits:

- 100% Z-Wave interoperable
- Perfect Gateway companion
- Best-in-class IR learning capability
- Built-in IR code library

### Specifications:

- Fully compliant to Z-Wave command class
- Supports up to 6 dedicated Z-Wave-to-IR channels
- Built-in wide angle IR emitters plus 5 addressable 3.5mm jacks for wired IR device deployment
- Programmable power level (LOW or HIGH) for each external IR emitter to avoid saturation of IR receivers
- Power Source: AC/DC Power adaptor 100~240Vac input, 5Vdc output
- Frequency:  
EU & UK: 868.4MHz;  
US/Canada: 908.4MHz;  
AU: 921.4MHz
- Dimension: 139 x 75 x 28.5 mm

	Supported Command Classes	Controlled	Supported
1	COMMAND_CLASS_CONFIGURATION	Yes	Yes
2	COMMAND_CLASS_CONFIGURATION_V2	No	Yes
3	COMMAND_CLASS_VERSION	No	Yes
4	COMMAND_CLASS_MANUFACTURER_SPECIFIC	No	Yes
5	COMMAND_CLASS_SIMPLE_AV_CONTROL	No	Yes
6	COMMAND_CLASS_BASIC 1	No	Yes
7	COMMAND_CLASS_POWERLEVEL	No	Yes
8	COMMAND_CLASS_MULTI_CHANNEL_V2	No	Yes



Specifications are subject to change without notice, due to continuing product improvement.

Ordering part number: BW8371

# Remotec

Workshop No. B2, 2/F., Block B, Tonic Industrial Centre,  
19 Lam Hing Street, Kowloon Bay, Hong Kong

Website: <http://www.remotec.com.hk>

Tel: (852) 2314 0330 Fax: (852) 2314 1006  
E-mail: [rtlsales@remotec.com.hk](mailto:rtlsales@remotec.com.hk)